



Revision	REV-02
Issue date	07.08.2026

TECHNICAL DATA SHEET

PEARL OIL STRATON 0W-30 SN

0W-30 |

STRATON 0W-30 SN is a high-performance SAE 0W-30 engine oil designed for modern gasoline and suitable light-duty diesel engines. It supports rapid lubrication during start-up, maintains viscosity stability under operating heat and helps reduce wear, sludge and deposits. Its balanced protection contributes to clean engine operation, controlled oil consumption and dependable performance in city, highway and mixed driving conditions.

MEETS & EXCEEDS

• API SN/SL	• API CF
• ACEA C2	• ACEA C3
• MB 229.31	• MB 229.51
• MB 229.52	• Porsche C30
• VW 504 00	• VW 507 00

TDS - TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUE
Density @15°C	ASTM D4052	0.847 g/cm ³
Kinematic Viscosity @40°C	ASTM D445	57.0 cSt
Kinematic Viscosity @100°C	ASTM D445	10.8 cSt
Viscosity Index	ASTM D2270	180
Flash Point	ASTM D92	232 °C
Pour Point	ASTM D97	-45 °C
CCS Viscosity	ASTM D5293	6100 cP
MRV Viscosity	ASTM D4684	20000 cP
NOACK Volatility	ASTM D5800	10.0 %
TBN	ASTM D2896	10.0 mgKOH/g
Sulphated Ash	ASTM D874	1.0 %

Typical values are indicative technical properties and are not specification limits.