



Revision	REV-02
Issue date	07.08.2026

TECHNICAL DATA SHEET

PEARL OIL LEGARA 10W-60 SL

10W-60 |

LEGARA 10W-60 SL is a robust SAE 10W-60 engine oil developed for gasoline, LPG and suitable diesel engines. It forms a durable lubricating film on critical components to help reduce wear and maintain protection under high temperatures and demanding operating conditions. The formulation supports viscosity stability, deposit and sludge control, and dependable daily performance for vehicles requiring the listed legacy API / OEM performance levels.

MEETS & EXCEEDS

- API SL
- API CF

TDS - TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUE
Density @15°C	ASTM D4052	0.868 g/cm³
Kinematic Viscosity @40°C	ASTM D445	170.0 cSt
Kinematic Viscosity @100°C	ASTM D445	24.0 cSt
Viscosity Index	ASTM D2270	170
Flash Point	ASTM D92	244 °C
Pour Point	ASTM D97	-30 °C
CCS Viscosity	ASTM D5293	6900 cP
MRV Viscosity	ASTM D4684	28000 cP
NOACK Volatility	ASTM D5800	8.5 %
TBN	ASTM D2896	10.5 mgKOH/g
Sulphated Ash	ASTM D874	1.3 %

Typical values are indicative technical properties and are not specification limits.