



Revision	REV-02
Issue date	07.08.2026

TECHNICAL DATA SHEET

PEARL OIL STRATON 5W-30 SN

5W-30 |

STRATON 5W-30 SN is a high-performance SAE 5W-30 engine oil designed for modern gasoline and suitable light-duty diesel engines. It supports rapid lubrication during start-up, maintains viscosity stability under operating heat and helps reduce wear, sludge and deposits. Its balanced protection contributes to clean engine operation, controlled oil consumption and dependable performance in city, highway and mixed driving conditions.

MEETS & EXCEEDS

• API SN/CF	• ACEA A3/B4
• MB 229.3 / 229.5	• VW 502 00 / 505 00
• BMW Longlife-01	• Renault RN 0700 / RN 0710
• Opel GM-LL-B-025	• PSA B71 2296

TDS - TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUE
Density @15°C	ASTM D4052	0.86 - 0.87 g/cm ³
Kinematic Viscosity @100°C	ASTM D445	9.3 - 12.5 cSt
Viscosity Index	ASTM D2270	Min. 135
Flash Point	ASTM D92	Min. 210 °C
Pour Point	ASTM D97	Max. -25 °C

Typical values are indicative technical properties and are not specification limits.