



Revision	REV-02
Issue date	07.08.2026

TECHNICAL DATA SHEET

PEARL OIL VELOS ATF DSG

ATF DSG | 1L

VELOS ATF DSG is a high-performance transmission fluid developed for applications matching the listed OEM fluid requirements. Its carefully balanced friction characteristics support smooth engagement and shift quality, while oxidation resistance and viscosity stability help protect gears, bearings, clutches and hydraulic control components over a wide operating-temperature range. Always select the fluid according to the vehicle or transmission manufacturer specification.

MEETS & EXCEEDS

• VW G 052 182	• VW G 052 512
• VW G 052 529	• VW G 055 529
• Ford WSS-M2C936-A	• MB 236.21
• BMW DCTF-1	

TDS - TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUE
Density @20°C	ASTM D4052	0.845 g/cm³
Kinematic Viscosity @40°C	ASTM D445	34.7 cSt
Kinematic Viscosity @100°C	ASTM D445	7.1 cSt
Viscosity Index	ASTM D2270	173
Flash Point	ASTM D92	204 °C
Pour Point	ASTM D97	-48 °C

Typical values are indicative technical properties and are not specification limits.