



Revision	REV-02
Issue date	07.08.2026

TECHNICAL DATA SHEET

PEARL OIL AXORA HYDRAULIC 32

32 | 16L

AXORA HYDRAULIC 32 is a high-quality anti-wear hydraulic fluid for systems requiring ISO VG 32 HLP/HM-type performance. It provides a stable lubricating film to protect pumps, valves and hydraulic components against wear, while oxidation resistance helps control deposits and extend fluid service life. Good air release, foam control, water separation and corrosion protection support smooth and reliable hydraulic operation.

MEETS & EXCEEDS

- | | |
|---------------------------|-------------------------------------|
| • DIN 51524-2 HLP | • ISO 11158 HM |
| • ISO 6743-4 HM | • Parker Denison HF-0 / HF-1 / HF-2 |
| • Bosch Rexroth RDE 90235 | |

TDS - TYPICAL TECHNICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUE
Density @15°C	ASTM D4052	0.86 - 0.87 g/cm³
Kinematic Viscosity @40°C	ASTM D445	32 cSt
Viscosity Index	ASTM D2270	Min. 100
Flash Point	ASTM D92	Min. 180 °C
Pour Point	ASTM D97	Max. -25 °C

Typical values are indicative technical properties and are not specification limits.